

Hobs

KH-6V13BS00




Highligths

- Key Lock
- Ceramic hob - 60 cm
- 3 radiant heaters
- Beveled front edge
- 1x14.5cm, 1x18cm, 1x27cm "3xZone"
- Tactile slider, 3 Timers
- Residual heat indicator

SHARP
Be Original.



Small to large size variation, our 3xZone allows true flexibility when it comes to selecting the perfect size for your pans.



Intuitive sliding controls allow you to select the power level easily.



Ideal for multi-cooking. So whether it's boiling, frying or sauteeing, you can set individual timers to switch off automatically.



Our ovens will let you know when the zone is at a safe temperature after cooking.



The smooth glass ceramic surface is especially easy to clean.



SHARP
Be Original.

Key Features

Colour	Black
Warranty (years)	2 years parts and labour
Construction type	Built-in
Width (cm)	60
Control type	Slider
Hob type	Vitroceramic
Cooking zones	3
Flexible zone	3xZone
Zone dimensions / Power (Boost W)	2 x 14.5 cm / 1200 W; 1 x 18 cm / 1800 W; 1 x 27 cm 3xZone / 2700 W
Total power	5.7
Control location	Front
Power levels	9
Frame	No
Bevel	Front Bevel
Width (cm)	60
Cooking zones (Nbr)	3
Zone dimensions (mm) / Power (W) (Boost W)	2 x 145 mm / 1200 W; 1 x 180 mm / 1800 W; 1 x 290 mm 3xZone / 2700 W
Total power (kW)	5.7
Power levels (Nbr)	9

Dimensions and Weight

Packing Dimensions (WxDxH) (mm)	620x133x578
Net Weight (kg)	9.5
Gross Weight (kg)	10.25
Cut-out dimensions (W x H x D) (mm)	560 x 490
Hob dimensions (W x H x D)	590 x 41 x 520
Brutto dimensions W x H x D (cm)	620 x 133 x 578
Net Weight (kg)	9.5
Hob dimensions W x H x D (cm)	590 x 41 x 520
Cut-out dimensions (W x H x D) (mm)	560 x 490
Brutto weight (kg)	10.25

European Article Number

EAN Code	4974019872230
----------	---------------

Power, consumption, and voltage

Voltage / Frequency (V) / (Hz)	220-240 / 50
Distribution line fuse / circuit breaker (A)	25

Accessories

Main cable Yes (1.1 m)

Spatula Sí

Functions

AutoHeat Control No

Stop & Go No

Timers 3

InductionBoost -

AutoHeatControl No

Timers (Nbr) 3

InductionBoost (Nbr) No

Safety

Pan detector No

Thermal cut off system Sí

Hot surface indicator Sí

Key lock Sí

Auto OFF Sí

Child lock(safety) Sí

AutoOFF Sí

Power, Consumption and Voltage

Voltage (V) / Frequency (Hz) 220-240 V / 50 Hz

Fuse rating (A) 25