Cookers

KF-76FVDD22IM-CH



Highligths

- Radiant
- Digital timer
- Easy to Clean Enamel
- 65 lt
- Full Outer Glass and Big Inner Glass Door
- 4 Wheel Guided Drawer





The smooth enamel interior helps make cleaning your oven easier.



Our ovens will let you know when the zone is at a safe temperature after cooking.



Our practical Vitroceramic/Radiant hobs are easy to use and can heat all your pans and pots quickly.



Key Features

Colour	INOX
Cleaning type	Easy to Clean Enamel
Heat type	Electric
Cavity volume (L)	65
Energy efficiency class	А
Control type	digital timer
Oven Opening	Drop opening
Removable inner glass door	No
Rack type	Enamel Molded Runners
Handle	juno
Hob type	radiant
Cooking zones	4
Zone dimensions / Power (Boost W)	2x145 - 2x180
Total power	8600
Contruction type	Freestanding
Size W × D (cm)	60x60
Oven Door	Full Outer Glass and Big Inner Glass Door
Deep Tray	1
Shallow Tray	1

Drawer Type

4 Wheel Guided Drawer

Dimensions and Weight

Gross Weight (kg)	44,2
Net dimensions W x H x D	60X85X60
Brutto dimensions W x H x D (cm)	645 x 684 x 922
Net Weight (kg)	42,1
Net dimensions W x H x D (mm)	600 X 850 X 600

Power, Consumption, & Voltage

Voltage / Frequency (V) / (Hz)	230 / 50
Fuse rating (A)	16A per phase

Power, consumption, and voltage

Energy consumption - static (kWh / cycle)	0.87
Energy consumption - fan forced	0.78

Accessories

Oven light	Yes
Main cable	5x1,5 without plug



Spatula	Ð
---------	---

No

Functions

Number of functions	8
Oven functions	
	L/D/T+B/T+B+F/B+F/G/DG/ DG+F
VapClean	No
PowerBoost	No
AutoCooking programs (number)	No
Temperature range (°C)	50-285

Safety

Door Lock	No
Hot surface indicator	Yes
Hob controls	knob

Power, Consumption and Voltage

Energy consumption - fan forced (kWh / cycle)	0.78
Voltage (V) / Frequency (Hz)	230V / 50Hz
Total power (W)	8600

Oven Features

Cavity inner surface	Easy to Clean Enamel
AutoCooking Programs (Nbr)	No
Removable inner door glass	No
Grid (Nbr)	1
Tray (Nbr)	Deep Tray: 1 / Shallow Tray: 1

Hob Features

Cooking zones (Nbr)	4
Zone dimensions (mm)	2x145 - 2x180

